



CUT LEVEL 6 HIGH-DEXTERITY NITRILE DIPPED GLOVES

HIGH DEXTERITY. MORE DURABLE.



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tearing	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

SMARTSWIPE™
Touch Screen
Compatible

Reinforced Nitrile Coating
Between Thumb & Forefinger

Long-Lasting Nitrile Grip

18 Gauge Knit
Total mobility

Light & Breathable Back

Color-Coded Bands
Easy cut level identification



SPECIFICATIONS

Gauge	18
Liner Material	HPPE Nylon Blend
Dip Material	Sandy Nitrile
Cuff Style	Elasticated Knit

RECOMMENDED APPLICATIONS

- High Dexterity Applications
- Demolition
- Wire Stripping
- Tile Cutting
- Concrete Work
- Sheet Metal, Duct & Glass Handling

CARE INSTRUCTIONS

Machine wash warm water (105°F), mild detergent, no bleach. Line dry.

SIZE	1 PAIR	12 PAIR (Contractor Pack)
S	48-73-7000	48-73-7000B
M	48-73-7001	48-73-7001B
L	48-73-7002	48-73-7002B
XL	48-73-7003	48-73-7003B
XXL	48-73-7004	48-73-7004B

SEE MORE PPE



or visit <https://qr.mke.tt/2hz48>

